

Hyosung

MS500S

Compact TCR for the Modern Branch.

At Hyosung, we leverage our expertise in cash recycling technology to enhance not only the self-service zone, but also the teller line. The MS500S delivers all of the functionality of the standard MS500S, but in a smaller form factor. This mini powerhouse includes features such as a transit cassette, self-audit, and continuous feed. Our approach in designing the MS500S was to ensure customers didn't have to choose between performance and size. Achieve the best of both worlds and elevate the teller experience.

Features

SECURE CASH TRANSFER

Our external transit cassette dramatically reduces cash exposure and is interchangeable with other Hyosung products:

- Verified operators can add and remove cash from the recycler without opening the safe
- Securely move cash inside the branch, from one device to another, and for CIT activities

SELF-AUDIT CAPABILITIES

Say goodbye to time-consuming manual cash counting.

- Single denomination audit
- Accurate and quick
- Audit anytime

FAST CASH COUNTING

With a built in currency counter, quick cash counts are easy

HIGH CAPACITY STORAGE

- 10,000 note total capacity*
- 100% stacking cassettes, no outdated RSM cassettes
- Recycling cassettes are denomination configurable to meet your unique needs

WINDOWS 10

Not all TCRs are created equal. Equip your branch with the best and most digitally secure system platform available.

CONTINUOUS FEED

The continuous feed capability allows for bulk deposit processing without slow down.

- The highest speed and continuous feed combine to make a big difference in branches where there are large commercial deposits





Hyosung MS500S

Specifications

Dimensions

- Height: 695mm (27.4") under desk
- Width: 428mm (16.85")
- Depth: 1,176.3mm (46.3")
- Weight: 420kg (926 lbs)

Environmental Conditions

- Temperature 5°C - 35°C (32°F - 104°F)
- Humidity 25% - 85%

System Platform

- Microsoft Windows® 10

Customer Interface

- 7" touch screen (15" optional)
- Display unit status, note counting, and guidance messages
- Error and jamming point display

Media Handling

- Continuous feed input module individual dispense and reject slots
 - 200-note dispense slot*
 - 30-note reject slot*
- Cash handling speed
 - Deposit - max. 12 notes per second
 - Dispense - max. 12 notes per second
- 8 recycling cassettes plus 1 overflow cassette
 - 8 Small-size recycling cassettes (100mm per cassette note capacity)
 - 1 Large-size overflow cassette (295mm note capacity)
- Self-audit capability

Power Supply

- AC 100V~240V±10% 50/60Hz

Security

- Safe - UL291 Level 1, CEN (optional)

Configuration Types

- Available Configurations
 - Cash Dispensing only
 - Cash Dispensing and Cash/Check deposit
 - Cash Recycling and Check deposit

Servicing

- Front access

Additional Features

- Securely moves cash within the branch or among different locations
 - External transit cassette (295mm note capacity)
 - Interchangeable with other Hyosung teller cash recyclers and branch transformation units
- In-use button
- Counting with note validation
- Note serial number recognition
- Fitness sorting
- Multi-channel communications

* Subject to media quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.